

AMENDMENTS TO THE CLAIMS:

1. (Currently Amended) An improved aiming device, comprising:

an aiming device comprising a surface showing a reference to a target; and,
a reflective surface being moveably mounted substantially axially with the
surface,

wherein ~~a user moves~~ the reflective surface is moveable by a user to site
the reference on the target,

wherein said reflective surface is angularly adjustable at various angles to
the reference, and

wherein said reflective surface is mounted to a base and a mounting
mechanism, said reflective surface rotates on said mounting mechanism in at least two
dimensions in relation to said base.

2. (Previously Presented) The improved aiming device of claim 1, further comprising a
base, attachable to a system to be aimed,

wherein the aiming device and the reflective surface are mounted.

3. (Previously Presented) The improved aiming device of claim 1, wherein the aiming
device comprises a holographic sight.

4. (Canceled)

5. (Previously Presented) The improved aiming device of claim 4, wherein the mounting mechanism comprises a socket mounted on the base and a ball joint connected rotatably to the socket, said ball joint is also connected to the reflective surface.

6. (Previously Presented) The improved aiming device of claim 1, further comprising a leveling mechanism attached to a base.

7. (Previously Presented) The improved aiming device of claim 6, wherein the leveling mechanism comprises a bubble level.

8. (Canceled)

9. (Canceled)

10-13 (Canceled)

14. (Previously Presented) The improved aiming device according to claim 1, wherein said reflective surface is angularly adjustable at various angles within at least two dimension in relation to the reference.

15. (Previously Presented) The improved aiming device according to claim 1, wherein said angles are viewing angles.

16. (Previously Presented) The improved aiming device according to claim 1, wherein the reflective surface is moveable in at least two dimensions.

17. (Previously Presented) The improved aiming device according to claim 1, further comprising a first line of sight between said reflective surface and said target, wherein a first angle exists between said first line of sight and said reflective surface.

18. (Previously Presented) The improved aiming device according to claim 17, wherein said first angle is between zero and ninety degrees vertically.

19. (Previously Presented) The improved aiming device according to claim 1, further comprising a second line of sight between said user and said reflective surface, wherein a second angle exists between said second line of sight and said reflective surface.

20. (Previously Presented) The improved aiming device according to claim 1, wherein said second angle is between minus ninety degrees and ninety degrees horizontally.

21. (Previously Presented) The improved aiming device according to claim 1, further comprising a first line of sight between said reflective surface and said target, and a second line of sight between said user and said reflective surface.

22. (Canceled)

23. (Previously Presented) The improved aiming device of claim 1, further comprising a magnifying lens mounted proximate to the first reflective surface

24. (Canceled)